

CERTIFICATE OF CALIBRATION

This Certificate certifies that the items listed below have been tested, manufactured, calibrated and/or inspected in accordance with IDEAL INDUSTRIES Networks Ltd. procedures. These procedures are ISO 9001:2015 controlled and are designed to assure that the instrument will meet its published specification.

Inspections and/or tests and Calibration have been performed, as applicable at or on behalf of

IDEAL INDUSTRIES Networks Ltd.

Stokenchurch House, Oxford Road Stokenchurch, High Wycombe

Buckinghamshire. HP14 3SX. UK

Calibration compliance is achieved by comparison to a calibrated standard, using an Automated Test Equipment (ATE) Station, in accordance with IDEAL LanTEK® System Factory Calibration Procedure 160626/160609 on file at the above address. Procedure 160637 details the method of calibration showing traceability of calibration of the ATE with a Network Analyser with calibration certificates documenting traceability to the National Physical Laboratory (NPL) and or National Institute of Standards and Technology (NIST).

C47D2K
VEMCO SP. Z O.O
LanTEK II-1000
1239015
1239030
`2.052
LanTEK ATE Calibration station (Serial No: 15)
28 June 2021
26 July 2022
Temperature: 23°C ± 2°C
2
karim ABOUD
IDEAL Industries GmbH Gutenbergstr. 10 D-85737 Ismaning, GERMANY Tel: +49-(0)89-99686-0 Fax: +49-(0)89-99686-111
Montag, 28. Juni 2021



C47D2K

CALIBRATION PROCEDURE:

The LanTEK tester consists of a Display and a Remote Handset, which is used to categorize data network links. The calibration of both units is carried out via an Automated Test Equipment (ATE), which uses internal calibration artefacts in a software controlled sequence to first calibrate the LF parameters (DC resistance, capacitance and length), followed by the calibration of the RF parameters (Return Loss, NEXT, FEXT and Insertion Loss). Both LF and RF measurements are carried out.

FACTORY CALIBRATION VALIDITY PERIOD:

IDEAL INDUSTRIES Networks Ltd. recommends a factory calibration every 12 months for LanTEK II & III series cable certifier. A new unit may be shipped with a period of up to 15 months of valid calibration. Units returned for annual calibration will be shipped with a 12 month calibration period.

Summary:

The unit is operational, all established measurement values are within the manufacture given tolerance

This calibration certificate may not be reproduced other than in full except with the permission of the issuing company, calibration certificates without signature are not valid.

1239015